

**CURED ON TYRES**

Tire size	Tread Pattern	Pattern Name	OEM	Rim OD	Tire Dimensions (inch)		Tire Dimensions (mm)		Tread Width (mm)	Finished tire weight (Kg)	Pcs/20ft
					Max Width	O.D +/- 2%	Max Width	O.D +/- 2%			
10X3	RIB	XT-R	JLG/Genie	203.2	3.1	10.0	78.0	254.0	75.0	7.3	2465
12X4	S	XT-S	Sky Jack	242	3.9	12.0	99.8	304.8	96.3	9 (without break) 10 (with break)	2000 1800
12X4	SMOOTH	SMOOTH	Sky Jack	242	3.9	12.0	99.8	304.8	96.3	9 (without break) 10 (with break)	2000 1800
12X4.5	TR	XT	Genie	255	4.5	12.0	114.2	304.8	111.5	14.2	1267
15X5	S	XT-S	Genie/Haulotte	318/320	5.0	14.9	127.0	379.0	122.0	21.2	850
15X5	TR	XT	Genie/Haulotte	318/320	5.0	14.9	127.0	379.0	122.0	21.2	850
15X5	TR	ULTIMA	Genie/Haulotte	318/320	5.0	14.9	127.0	379.0	122.0	21.2	850
16X5	RIB	XT-R	Sky Jack	336	4.7	16.0	119.8	406.4	114.0	17.8 (without break) 19.6 (with break)	1011 918
323X100	S	XT-S	JLG	280	3.9	12.8	100.0	323.9	93.0	9.7	1855
406X125	S	XT-S	JLG	354	4.9	16.0	125.0	407.2	121.0	18.0	1000

**Tire Load Capacities**

Tire size	Counter balanced Lift Truck		
	Static Up to 0 Km/h	Up to 6Km/h	Up to 10Km/h
10X3	880	690	455
12X4	1215	1084	970
12X4.5	1215	1084	970
15X5	1615	1450	1290
16X5	2015	1430	1050
323X100	1345	955	700
406X125	2015	1430	1050