

OTR Pneumatic Range

Tire size	Ply rating	Tire type	Rim size (inch)	OD (mm)	SW (mm)	Inflation Pressure (PSI/Kpa)	Max Load (Kgs/lbs)	Max Speed (KPH/MPH)	Tread pattern
14.00-24	20	TT/TL	10	1369	374	68/475	4625/10196	50/30	LOADER GRIP E3/L3
	24					83/575	5150/11350	50/30	
	28					94/650	5600/12340	50/30	
15.5-25	16	TL	12	1278	394	47/325	3750/8250	50/30	LOADER GRIP E3/L3
16.00-25	28	TT/TL	11.25	1521	431	83/570	6700/14770	50/30	LOADER GRIP E3/L3
	32					94/650	7300/16100	50/30	LOADER GRIP E4
17.5-25	20	TT/TL	14	1347	440	58/400	5000/11000	50/30	LOADER GRIP E3/L3 LOADER GRIP E3/L3 N
18.00-25	36	TT/TL	13	1643	500	123/850	7250/16000	50/30	LOADER GRIP E3/L3
20.5-25	20	TT/TL	17	1490	524	47/325	6000/13200	50/30	LOADER GRIP E3/L3 LOADER GRIP E3/L3 N
	24					58/400	6700/14770	50/30	
23.5-25	20	TT/TL	19.5	1616	596	44/300	7300/16100	50/30	LOADER GRIP E3/L3 LOADER GRIP E3/L3 N
	24					51/350	8000/17600	50/30	
	28					58/400	8750/19290	50/30	
26.5-25	24	TT/TL	22	1746	659	36/250	8250/18188	50/30	LOADER GRIP E3/L3
	28					51/300	9250/20392	50/30	
	32					51/350	10000/22000	50/30	